

# TECHNICAL SPECS

## MTB RIMS

Model	World Cup 29"	Carbon Team 29"	Flash Carbon 29"	Flash Carbon 27.5"
Rim Material	Full Carbon	Full Carbon	Full Carbon	Full Carbon
Rim Width Outer	33mm	30mm	36mm	36mm
Rim Width Inner	27mm	25mm	30mm	30mm
Profile	30mm	26mm	28mm	28mm
Tire Type	Tubeless ready	Tubeless ready	Tubeless ready	Tubeless ready
Asymmetric	Yes	Yes	Yes	Yes
Hookless	Yes	Yes	Yes	Yes
E.T.R.T.O.	622 x 27C	622 x 25C	622 x 30C	584 x 30C
ERD	-	-	-	-
Drilling	28	28	28	28
Max Spoke Tension	1600 Nm	1600 Nm	1800 Nm	1800 Nm
Discipline	Racing: XCO / XCM	Racing: XCO / XCM	E-Bike / AM	E-Bike / AM
Max. Pressure	60 psi	40 psi	40 psi	40 psi

Model	Carbon Zer0 29"	Zenith Team 29"	Zenith 29"	RW 29"
Rim Material	Full Carbon	Aluminium	Aluminium	Aluminium
Rim Width Outer	31mm	28mm	25mm	28mm
Rim Width Inner	25mm	25mm	21mm	23mm
Profile	25mm	16mm	18mm	18mm
Tire Type	Tubeless ready	Tubeless ready	Tubeless ready	Tubeless ready
Asymmetric	Yes	Yes	Yes	No
Hookless	Yes	Yes	No	No
E.T.R.T.O.	622 x 25C	622 x25C	622 x 21C	622 x 23C
ERD	-mm	603mm	599mm	604mm
Drilling	28	32	32	32
Max Spoke Tension	1900 Nm	1400 Nm	1500 Nm	1600 Nm
Discipline	XCO / XCM	Racing: XCO / XCM	XCO / XCM	XCO / XCM / AM
Max. Pressure	40 psi	40 psi	40 psi	40 psi

Model	Zer0 29"
Rim Material	Aluminium
Rim Width Outer	24
Rim Width Inner	19
Profile	18
Tire Type	Tubeless ready
Asymmetric	No
Hookless	No
E.T.R.T.O.	622 x 19C
ERD	599mm
Drilling	32
Max Spoke Tension	1400 Nm
Discipline	XCO / XCM
Max. Pressure	40 psi